


Serie Heavy

307E Nylon Cable Chain with alu-drawn frames

Inner height (D) 46,5 mm

Strong side-bands chain with dovetailed links and triple low friction pins, Alu-drawn frames mounted each second pitch full-pitch frames version available on demand, Special C size available on demand, Vertical and horizontal separator systems are available.



Separator	
- Unassembled	Part.no S307EF
- Assembled	Part.no S307EFMC
Pin	
	Part.no PG307

Technical characteristics when self-supported

Speed	8 m/s
Acceleration	40 m/s ²


For higher requirements please consult our technical dept.

A	B	C	D	R	Weight/m	Chain
mm	mm	mm	mm	mm	kg	Part Number
113	65	75	46,5	075-090-120-140-170-200-250	1,95	307E075□□□□*
138	65	100	46,5	075-090-120-140-170-200-250	2,00	307E100□□□□*
188	65	150	46,5	075-090-120-140-170-200-250	2,15	307E150□□□□*
238	65	200	46,5	075-090-120-140-170-200-250	2,25	307E200□□□□*
288	65	250	46,5	075-090-120-140-170-200-250	2,35	307E250□□□□*
338	65	300	46,5	075-090-120-140-170-200-250	2,50	307E300□□□□*
C+38	65	46,5	075-090-120-140-170-200-250		307E□□□□□□**

Complete the code by inserting the value of the radius (R); Ex. 307E075□□□□

Complete the code by inserting the value of the quote C and the radius (R); Ex. 307E□□□□□□□□

Chain equipped with alu-drawn frames full-pitch: complete the code by inserting the letter D. Ex. 307E075120□□



Length of chain (L)
Half travel distance ($\frac{LS}{2}$)
plus length of curve (M)

$$L = \frac{LS}{2} + M$$


R	H	N	M
mm	mm	mm	mm
075	219	180	380
090	249	195	425
120	309	225	520
140	349	245	580
170	409	275	675
200	469	305	770
250	569	355	930



Version alu-drawn frames mounted each second pitch.

Self-Supporting Capacity Diagram

The maximum length of the self-supporting capacity ($\frac{LS}{2}$) in relationship to the weight of the cables and hoses contained per linear metre.



End Brackets

The end brackets set allows the two ends of the chain to be attached to the equipment. Set complete with tiewrap clamps available on request.

Nylon Type




Fig. A The chain can be fixed frontally, inner or outer radius. (Fig A)

Bright Zinc Plated Steel Type***






Fig. B Chain fixed outside the radius. (Fig B) See end brackets mounting variations page 31.




The red marking in the diagram area considers the difference of weight between various widths of chains assembled with alu-drawn frames every second pitch.

For applications with $\frac{LS}{2}$ and weights not included in the area of the diagram showing self-supporting capacity, verify the possible use of support rollers (see page 30).



Chain Type	F mm
307E075	94
307E100	119
307E150	169
307E200	219
307E250	269
307E300	319

Special widths F=A-19



Chain Type	F mm
307E075	64
307E100	89
307E150	139
307E200	189
307E250	239
307E300	289

Special widths F=A-49

Nylon Type Part Numbers

Complete Set Assembled	End Brackets
Chain	Set
Type	Set
307E...	AN307KM

Complete Set Unassembled	End Brackets
Chain	Set
Type	Set
307E...	AN307K

Bright Zinc Plated Steel Type Part Numbers

Complete Set Assembled	End Brackets
Chain	Set
Type	Set
307E...	A307EKM**

Complete Set Unassembled	End Brackets
Chain	Set
Type	Set
307E...	A307EK**

Tiewrap Clamp

Assembl. SFCT307E□□□□*KM
Unassembl. SFCT307E□□□□*K

* Inner width (C)

** 1=Pos.1; 2=Pos.2; 3=Pos.3

*** Available on request in stainless steel




Serie Heavy

307E Nylon Cable Chain with alu-drawn frames



How to open alu-drawn frames



How to open alu-drawn frames



Supplementary movable separators.

Special tool to remove the connecting pivots:
Part Number P2036.



For further information please consult Brevetti Stendallo's Technical Office